



AUTODECK 1, AUTODECK 2 & AUTODECK 5 PRODUCT SPECIFICATIONS

Individual Module Size:	1ft x 1ft x 0.5”H / 30.48 cm x 30.48 cm x 1.27 cm
Assembled Section Size:	3ft x 3ft x 0.5”H / 91.44 cm x 91.44 cm x 1.27 cm
Module Weight:	AD1: Open Tile – 11.6 oz / 0.328 kg / 328.85 grams AD2: Smooth Tile – 15.2 oz / 0.430 kg / 430.91 grams AD4: Vinyl Laminate Tile – refer to separate spec sheet AD5: Diamond-Plate Tile – 15.6 oz / 0.442 kg / 442.25 grams
Base Material:	Polypropylene co-polymer High-impact material
Standard Colors:	Black, White, Orange, Yellow, Brown, Burgundy, Green, Beige, Silver, Blue, Red, Light Gray, Dark Gray, Light Blue.
Weight Support:	20,000 lbs sq/ft. Varies depending on subsurface.
Fire Rating:	UL 94HB (Underwriters laboratory Yellow Card Number) This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2” per minute for a 2” wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.
Connection System:	Male/Female, clip-and-loop connection system. Snaps together with no tools. Seven (7) connectors and receptors on each 1ft module side for added stability and redundancy.
Features:	Lightweight design. Water flows underneath floor. Connects and disconnects easily. Stores compactly. Suitable for indoor and outdoor use.
Edging:	1ft sections snap directly to perimeter of dance floor tile. Utilizes same clip-and-loop connection system. Provides gradual transition onto dance floor.
Warranty:	10-year warranty against manufacturer’s defects.



AUTODECK 4 - PRODUCT SPECIFICATIONS

Individual Module Size:	1.01ft x 1.01ft x 0.563”H / 30.79 cm x 30.79 cm x 1.43 cm
Assembled Section Size:	3.03ft x 3.03ft x 0.563”H / 92.39 cm x 92.39 cm x 1.43 cm
Weight:	Individual Module: 1.52 lbs. / 0.689 kg. / 689.46 grams Assembled Section: 13.68 lbs. / 6.2 kg.
Base Material:	Polypropylene co-polymer High-impact material Standard color: Black (White can be special ordered)
Surface Material:	Vinyl No-Wax Tile
Colors:	Standard Colors: Dark Oak, Light Oak, Black and White. Custom colors available.
Fire Rating:	UL 94HB (Underwriters laboratory Yellow Card Number) This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2” per minute for a 2” wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.
Connection System:	Male/Female, clip-and-loop connection system. Snaps together with no tools. Seven (7) connectors and receptors on each 1ft module side for added stability and redundancy.
Features:	Lightweight design. Water flows underneath floor. Connects and disconnects easily. Stores compactly. Suitable for indoor and outdoor use. Slotted tray holds laminate for added strength.
Edging:	1.01ft sections snap directly to perimeter of dance floor tile. Utilizes same clip-and-loop connection system. Provides gradual transition onto dance floor.
Warranty:	10-year warranty against manufacturer’s defects.