



PRODUCT SPECIFICATIONS

Standard Module Size: 8' x 4' (2.44m x 1.22m) / 32 sq/ft (2.973 sq/m)
Module Weight per Square Foot: 2.69 lbs. / 43 oz. / 1.22 kg. / 1219 grams
Module Weight per Square Meter: 28.60 lbs. / 12.97 kg.

Product:	Traction Surfaces:	Thickness:
DD1	Rugged / Rugged	1/2" mat + 3/8" cleat + 3/8" cleat = 1 1/4" total
DD2	Pedestrian / Rugged	1/2" mat + 3/8" cleat = 7/8" total
DD3	Pedestrian / Smooth	1/2" total
DD4	Rugged / Smooth	1/2" mat + 3/8" cleat = 7/8" total

Rugged Traction Surface: Double-traction tread design includes two parallel traction treads positioned at a 90-degree angle to adjacent double traction tread sets.

Pedestrian Traction Surface: Pedestrian friendly alternating cross shaped traction design.

Smooth Surface: No traction pattern for easier cleaning and maintenance

Module Size:	Module Weight:
8' x 4' (2.44m x 1.22m)	86lbs (39.01kg)
8' x 3' (2.44m x 0.91m)	64.5lbs (29.26kg)
6' x 3' (1.83m x 0.91m)	48.42lbs (21.96kg)
8' x 2' (2.44m x 0.609m)	43lbs (19.5 kg)

- Colors:** Black, White.
Custom colors available (minimum order required).
- Material:** Black High-Density Polyethylene (HDPE) post-industrial recycled plastic, naturally UV resistant due to the carbon black used for color. White UV-stabilized mats available.
- Weight Loading:** Varies, depending on sub-surface, up to 80 tons capacity.
- Compressive Strength:** 2,843 psi (ASTM D695-02a)
- Flammability Resistance:** UL-94 HB Rating
- Ground Surface:** DuraDeck mats are designed to be used with no ground preparation over grass, gravel, soil, concrete, asphalt, mud and sandy soil conditions.
- Connection System:** DuraDeck mats have eight holes: one in each corner and four in the center line (two on each 8ft side) to create multi-directional roadways of nearly any size or shape. Mats can be connected using metal DuraLink connectors. DuraLinks do not require tools to install.
- Shipping:** Pallet maximum is 30 units (4' x 8')
20' Ocean Container: 250 – 4' x 8' unit order and/or equal to 29,240lbs.
40' Ocean Container: 500 – 4' x 8' unit order and/or equal to 43,000lbs.
- Warranty:** 7 years against cracking and breaking under normal use.