

EventDeck

PRODUCT SPECIFICATIONS

Module Size:	Width: 4" / 10.16 cm / 101.6 mm Length: 12" / 30.48 cm / 304.80 mm 3 connected modules = 12" x 12" / 304.8 mm x 304.8 mm Thickness: ¾" Tall / 1.91 cm / 19.05 mm
Module Weight:	0.27 lbs. / 4.3 oz. / 0.12 kg. / 122 grams Per Square Foot: 0.81 lbs. / 12.96 oz. / 0.37 kg. / 367.41 grams Per Square Meter: 8.72 lbs. / 3.95 kg.
Material:	High-impact polypropylene co-polymer. UV Inhibitors added.
Fire Rating:	UL 94HB (Underwriters Laboratory Yellow Card Number) This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers. ASTM 2859 (Flammability of Finished Texture Floor Covering Materials) – passed test * Testing reports available for fire ratings
Hot Wire Ignition Rating:	3
Melting Point:	324 Fahrenheit / 162 Celsius Operating Range: -10° F → 150°F / -23.33° C → 65.56° C
Support Structure:	Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads. There are no open spans (without ribs) greater than 2.125".
Weight Loading:	8,000 lbs sq/ft static load, solid sub-surface. Varies depending on sub-surface.
Ground Surfaces:	EventDeck is designed to be used with little ground preparation over grass, gravel, sand, soil, concrete, asphalt, ice, snow, mud, synthetic turf, rubberized tracks, and other standard surfaces.
Shipping:	40" x 48" Pallet: up to 1,000 sq/ft 463L Pallet: 7,776 sq/ft 20' Ocean Container: 12,340 sq/ft 40' Ocean Container: 27,380 sq/ft Note: High cube container loads can be loaded with additional product.

Functional Features:

- a) Sections are designed to roll up for easy installation, removal, storage and transport.
- b) Individual modules interconnect to form larger flooring sections.
- c) Connection system allows for installation and disassembly *without* the need for connection or separation tools.
- d) Modules feature integrated, multi-directional cable channels on the underside of each tread, for running power and communication wiring or rope lighting.
- e) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
- f) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

Grass Protection Features (ED1):

- a) Modules feature an integrated moisture canopy which allows for moisture retention.
- b) EventDeck features direct-from-the-top drainage holes that provide drainage, ventilation, air, and small amounts of light to grass below.
- c) Underside is specially designed to protect grass and other sensitive surfaces by distributing weight across multiple support ribs. No sharp, unsupported edges exist to damage grass or synthetic turf.

Warranty:

3-year warranty against manufacturer's defects.

National Stock #:

8340-01-525-4069

EVENTDECK ACCESSORIES SPECIFICATIONS

Edging Specifications:

Edging size is 3" x 12" x 3/4" (tapered). Edging is designed to attach to flooring modules both lengthwise and widthwise, providing a gradual tapered edge. Edging extends flat 1" from end of flooring module and then slopes down to ground over a 2" span.