



## PRODUCT SPECIFICATIONS

<b>Module Size:</b>	3.00 sq/ft in Hexagonal configuration – 26” wide at widest point Height: 1.9”
<b>Module Weight:</b>	6 lbs. / 96 oz. / 2.72 kg. / 2772 grams <b>Per Square Foot:</b> 2 lbs. / 32 oz. / 0.91 kg. / 907 grams <b>Per Square Meter:</b> 21.5 lbs. / 9.75 kg.
<b>Material:</b>	High-Density Polyethylene. UV Inhibitors added.
<b>Fire Rating:</b>	UL 94HB (Underwriters Laboratory Yellow Card Number) This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2” per minute for a 2” wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.  ASTM 2859 (Flammability of Finished Texture Floor Covering Materials) – passed test * Testing reports available for fire ratings
<b>Hot Wire Ignition Rating:</b>	3
<b>Melting Point:</b>	324 Fahrenheit / 162 Celsius
<b>Support Structure:</b>	Flooring module incorporates multi-directional, concentric, structural support ribbing, allowing for distribution of weight and loads. Reinforcement ribbing width is 0.14” (over 1/8”).
<b>Weight Loading:</b>	30,000 lbs. sq/ft static load, solid sub-surface Suitable for light and heavy pedestrian and vehicle use on multiple ground surfaces.
<b>Functional Features:</b>	a) Tiles are designed to nest into each other, locking each tile down and together using a unique over-and-under connection system.  b) Individual modules interconnect to form larger flooring sections. Sections can be added to any side of the HexaDeck module.  c) Connection system allows for assembly and disassembly <i>without</i> the need for separation tools. There are no loose parts – each tile is a complete piece and required no additional pieces to function alone or in conjunction with adjacent sections.  d) Tile features diamond-plate finish for added slip resistance and drainage holes to prevent water build-up.

**Grass Protection**

**Features:**

- a) Tiles feature an integrated moisture canopy that allows for moisture retention.
- b) HexaDeck incorporates drainage holes that provide ventilation, air and small amounts of light to grass below.
- c) Underside is specially designed to protect grass by distributing weight across multiple support ribs. No sharp, unsupported edges exist to damage grass or synthetic turf.
- d) Module canopy is raised 1.85 inches off of ground surface.

**Warranty:**

3-year warranty against manufacturer's defects.