



Division 9

Resilient Athletic Surfacing

(RUBBERDECK SUPERTILE – RECYCLED RUBBER MOLDED TILES)

SPECIFICATIONS

	Page
1. General.....	2
1.1 Description	2
1.2 References	2
1.3 System Description	3
1.4 Quality Assurance	3
1.5 Submittals	4
1.6 Delivery, Storage, and Handling	5
1.7 Warranty	5
1.8 Working Conditions	5
2. Products.....	6
2.1 Manufacturer	6
2.2 Proprietary Product(s)	6
2.3.1 RubberDeck SuperTile Recycled Rubber Molded Tiles	6
2.3.2 SignaGrip One-Component Polyurethane Adhesive	8
2.4 Product Substitutions	9
2.5 Related Materials	9
2.6 Source Quality	9
3. Execution.....	9
3.1 Manufacturer's Instructions	9
3.2 Examination	9
3.3 Preparation	10
3.4 Erection / Installation / Application / Construction	10
3.5 Field Quality Requirements	10
3.6 Cleaning	10
3.7 Protection	10
3.8 Schedules	10
3.9 Maintenance	11



PART 1 – GENERAL

1.1 DESCRIPTION

- A. The work of this section includes:
 - 1. RubberDeck SuperTile Recycled Rubber Molded Tiles
 - 2. Adhesives

- B. Related Sections: Section(s) related to this section include:
 - 1. The work specified in this Section consists of the installation of RubberDeck SuperTile in accordance with these specifications, and in conformity with the dimensions and notes shown in the plans.

1.2 REFERENCES

- A. Standards listed by reference, including revisions by issuing authority, form a part of this specification section to extent indicated. Standards listed are identified by issuing authority, authority abbreviation, designation number, title, or other designation established by issuing authority. Standards subsequently referenced herein are referred to by issuing authority abbreviation and standard designation.

- B. American Society for Testing and Materials (ASTM):
 - 1. ASTM D412 Standard Test Methods for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers – Tension
 - 2. ASTM F137 Standard Test Method for Flexibility of Resilient Flooring Materials with Cylindrical Mandrel Apparatus
 - 3. ASTM F970 Standard Test Method for Static Load Limit
 - 4. ASTM D2047 Standard Test Method for Static Coefficient of Friction of Polish-Coated Floor Surfaces as measured by the James Machine
 - 5. ASTM F925 Standard Test Method for Resistance to Chemicals of Resilient Flooring
 - 6. ASTM C423 Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method
 - 7. ASTM C518 Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus
 - 8. ASTM E492 Standard Test Method for Laboratory Measurement of Impact Sound Transmission Through Floor-Ceiling Assemblies Using the Tapping Machine
 - 9. ASTM E413 Classification for Rating Sound Insulation
 - 10. ASTM E2129 Standard Practice for Data Collection for Sustainability Assessment of Building Products
 - 11. ASTM D5116 Standard Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions From Indoor Materials/Products
 - 12. ASTM F150 Standard Test Method for Electrical Resistance of Conductive and Static Dissipative Resilient Flooring
 - 13. ASTM D297 Standard Practice for Rubber Products – Chemical Analysis
 - 14. ASTM D3676 Standard Specification for Rubber Cellular Cushion used for Carpet or Rug Underlay



15. ASTM D395 Standard Test Methods for Rubber Property – Compression Set
 16. ASTM F710 Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring
 17. ASTM F1869 Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride
 18. ASTM F1292 Standard Specification for Impact Attenuation of Surfacing Materials within the Use Zone of Playground Equipment
- C. American Association of Textile Chemists and Colorists
1. Technical Manual 134 Electrostatic Propensity of Carpets
- D. Federal Test Method Standard 101B Test Methods for Packaging Materials
1. Method 4046 Electrostatic Properties of Materials
- E. Collaborative of High Performance Schools (CHPS) Section 01350
1. Low-emitting materials criteria for use in a typical classroom
- F. South Coast Air Quality Management District (SCAQMD) Rule #1168
1. VOC standards for adhesive and sealant applications
- G. Leadership in Energy and Environmental Design - LEED®
1. International Organization for Standardization® document, ISO 14021 – Provides guidance on the terminology, symbols, testing, and verification methodologies that an organization should use for self-declaration of the environmental aspects of its products and services.

1.3 SYSTEM DESCRIPTION

- A. Performance Requirements: Provide recycled rubber resilient flooring, which has been manufactured and installed to maintain performance criteria stated by manufacturer without defects, damage, or failure.

1.4 QUALITY ASSURANCE

- A. Qualifications:
1. Installer Qualifications: Installer experienced in performing work of this section who has specialized in installation of work similar to that required for this project.
 - a. Certificate: When requested, submit certificate, indicating qualification.
 2. Manufacturer's Qualifications: Manufacturer capable of providing field service representation during construction and approving application method.
- B. Regulatory Requirements: (Specify applicable requirements of regulatory agencies.)
- C. Mock-Ups: Install at project site a job mock-up using acceptable products and manufacturer-approved installation methods. Obtain Owner and Architect's acceptance of finish color,



texture and pattern and workmanship standard. Comply with Division 1 Quality Control (Mock-up Requirements) Section.

1. Mock-Up Size: (Specify mock-up size.)
2. Maintenance: Maintain mock-up during construction for workmanship comparison; remove and legally dispose of mock-up when no longer required.
3. Incorporation: Mock-up may be incorporated into final construction upon Owner's approval.

D. Pre-installation Meetings: Conduct pre-installation meeting to verify project requirements, substrate conditions, manufacturer's instructions, and manufacturer's warranty requirements. Comply with Division 1 Project Management and Coordination (Project Meetings) Section.

E. Pre-installation Testing: Conduct pre-installation testing as follows: (Specify substrate testing; consult with flooring manufacturer.)

1.5 SUBMITTALS

A. General: Submit listed submittals in accordance with Conditions of the Contract and Division 1 Submittal Procedures Section.

B. LEED: Provide documentation of how the requirements for credit will be met.

1. List of proposed materials with recycled content. Indicated pre-consumer and post-consumer content.
2. Product data and certification letter indicating percentage of recycled content for both pre-consumer and post-consumer content.
3. Recycled content is defined in accordance with the International Organization for Standardization document, ISO 14021 Environmental labels and declarations.
 - a. Post-consumer material – waste materials diverted from the waste stream after consumer or commercial use.
 - b. Pre-consumer material – materials diverted from the waste stream during the manufacturing process. Excluded are regrind, rework, and scrap.

C. Product Data: Submit product data, including manufacturer's guide specifications product sheet, for specified products.

D. Shop Drawings: Submit shop drawings showing layout, profiles and product components, including anchorage, accessories, finish colors, patterns, and textures.

E. Samples: Submit selection and verification samples for finishes, colors, and textures.

F. Quality Assurance Submittals: Submit the following:

1. Test Reports: Certified test reports showing compliance with specified performance characteristics and physical properties.
2. Certificates: Product certificates signed by manufacturer certifying materials comply with specified performance characteristics, criteria, and physical requirements.
3. Manufacturer's Instructions: Manufacturer's installation instructions.



4. Manufacturer's Field Reports: Manufacturer's field reports specified herein.
- G. Closeout Submittals: Submit the following:
1. Operation and Maintenance Data: Operation and maintenance data for installed products in accordance with Division 1 Closeout Submittals (Maintenance Data and Operational Data) Section. Include methods for maintaining installed products and precautions against cleaning materials and methods detrimental to finishes and performance.
 2. Warranty: Warranty documents specified herein.

1.6 DELIVERY, STORAGE & HANDLING

- A. General: Comply with Division 1 Product Requirements Sections.
- B. Ordering: Comply with manufacturer's ordering instructions and lead time requirements to avoid construction delays.
- C. Delivery: Deliver materials in manufacturer's original, unopened, undamaged containers with identification labels intact.
- D. Storage and Protection: Store materials at temperature and humidity conditions recommended by manufacturer and protect from exposure to harmful weather conditions.

1.7 WARRANTY

- A. Project Warranty: Refer to Conditions of the Contract for project warranty provisions.
- B. Manufacturer's Warranty: Submit, for Owner's acceptance, manufacturer's standard warranty document executed by authorized company official. Manufacturer's warranty is in addition to and not a limitation of, other rights Owner may have under Contract Documents.
 1. Warranty Period: (Specify term) years commencing in Date of Substantial Completion.

1.8 WORKING CONDITIONS

- A. Temperature Requirements: Maintain air temperature in spaces where products will be installed for time period before, during, and after installation as recommended by manufacturer.
- B. Field Measurements: Verify actual measurements/openings by field measurements before fabrication; show recorded measurements on shop drawings. Coordinate field measurements and fabrication schedule with construction progress to avoid construction delays.



PART 2 – MANUFACTURER / PROPRIETARY PRODUCT(S)

2.1 MANUFACTURER

- A. Address: Signature Fencing and Flooring Systems LLC.
50 East 42nd Street 14th Floor New York, NY 10017:
Telephone: (212) 953-1116, (800) 705-1544: Fax (212) 953-1117
Email: info@signaturesportsflooring.com

2.2 PROPRIETARY PRODUCT(S)

- A. RubberDeck SuperTile Recycled Rubber Molded Tiles and Adhesives manufactured by Signature for indoor commercial applications.
1. 1" RubberDeck SuperTile Recycled Rubber Molded Tiles
 2. SignaGrip, a one-compound polyurethane adhesive

2.3.1 RUBBERDECK SUPERTILE RECYCLED RUBBER MOLDED TILES

- A. Product Name: The factory molded modular surfacing system furnished under this specification shall be Signature's RubberDeck SuperTile Recycled Rubber Molded Tiles.
- B. Physical: 1" RubberDeck SuperTile configurations consist of a high density, wear surface; cylindrical support feet that allow underside cable routing, maximum resiliency, and water drainage, as well as twelve molded perimeter dowel holes that accept specially designed barbed dowel pins to promote ease of installation.
- C. Material: Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber, with reprocessed ColorMill® EPDM granules bound in both underlayment and wear surfaces with a wear and weather resistant polyurethane.
- D. Component: 1" SuperTile is a factory-molded surface composed of high quality rubber granules bound with a wear and weather resistant polyurethane. The polyurethane binder is composed of MDI (diphenylmethane diisocyanate) isocyanate and polyether (polypropylene glycol) polyols. TDI (toluene diisocyanate) isocyanate or catalysts based on lead or mercury are not utilized. Rubber



granules are blends of ground rubber particulates specially blended to enhance tile strength, durability, and energy absorption characteristics. All coloring pigments are inorganic oxides. Pigments based on cadmium are not utilized.

- E. Tile Dimension: RubberDeck UltraTile products shall be _____ (specify: 24" x 24") and an overall thickness of _____ (specify: 1" (25.4mm) standard).
- F. Tile Weight: 4.0 lb/ft² (19.5 kg/m²)
- G. Tile Standard Tolerances: Width: ± 2 mm
Thickness: ± 3 mm
- H. Colors: Specify color from manufacturer's standard colors, custom colors, or special logo/graphic inlays.
- I. Wear Surface Density: 60.0 lbs/cu. ft. min.
- J. Coefficient of Thermal Expansion: 1.10 x 10⁻³ in./ft.-°F
- K. Void Volume: 13% min.
- L. Water Permeation Rate: 0.045 cm./sec.
- M. Tear Resistance: 13.13 kN/m (ASTM D624, Die C)
- N. Abrasion: .1 or 0.20 mg loss/cycle (ASTM D3389, 2000 cycles, H18 Wheels)
- O. Accelerated Aging: 105% Tensile Retention, 87% Elongation Retention (DIN 1835 Part 6, 2000 hrs. H18 Wheels)
- P. Tensile Strength: 200lb/in² min. (ASTM D412)
- Q. Flexibility: Pass ¼" mandrel (ASTM F137)
- R. Static Load Limit: 400 lb/in² < 0.005 in. (ASTM F970)
- S. Coefficient of Friction: > 0.9 (ASTM D2047)
- T. Chemical Resistance: 5% Acetic Acid, no change (ASTM F925)
70% Isopropyl Alcohol: no change
5% Sodium Hydroxide: no change
5% Hydrochloric Acid: no change
5% Ammonia: no change



	Bleach; no change 5% Phenol: no change Sulfuric Acid: no change
U. Noise Reduction Coefficient:	0.10 sabine/ft ² (ASTM C423)
V. Thermal Conductivity:	Approximately 0.406 Btu-in/hr-ft ² -°F (ASTM C518)
W. Impact Insulation Class:	49 (ASTM E492)
X. Sound Transmission Coefficient:	51 (ASTM E413)
Y. Sustainability:	Data collected (ASTM E2129)
Z. VOC Washington State IAQ Test:	Pass (ASTM D5116)
AA.CHPS/CA 01350:	Pass (ASTM D5116)

2.3.2 SIGNAGRIP ONE-COMPONENT POLYURETHANE ADHESIVE

A. Product Name:	The one-part urethane adhesive under this specification shall be Signature's SignaGrip one component polyurethane adhesive.
B. Material:	SignaGrip is a one-component polyurethane moisture cured, non-sag, permanently elastic adhesive that has excellent adhesion to elastomers, concrete, and wood and is engineered for indoor and outdoor applications.
C. Adhesive Type:	One-component polyurethane
D. Adhesive Cure System:	Moisture cured
E. Weight:	4 gallon pail - 56 lbs 2 gallon pail - 28 lbs 10.1 oz. cartridge
F. Color:	Medium grey
G. VOC Content:	0 lb/gal calculated
H. Freeze/Thaw:	Stable
I. Application Temperature:	40° F - 100° F



J. Calcium Chloride Test:	Maximum 5.5 lbs per 1,000 sq. ft. in 24 hrs (ASTM F1869)
K. Flashpoint:	> 500° F
L. Shelf Life:	12 months
M. Working Time:	30-40 minutes
N. Trowel:	1/16" square notched trowel ⁽¹⁾
O. Coverage Rate:	95 ft ² per gallon (1/16" square-notched trowel)
P. SCAQMD Rule #1168:	0 lbs/gal.

⁽¹⁾ For indoor installation on concrete or plywood subfloors only. See Signature Sports Flooring Installation Manual for instructions.

2.4 PRODUCT SUBSTITUTIONS

A. Substitutions: No substitutions permitted.

2.5 RELATED MATERIALS

A. Related Materials: Refer to other sections listed in Related Sections paragraph herein for related materials.

2.6 SOURCE QUALITY

A. Source Quality: Obtain recycled rubber resilient flooring materials from a single manufacturer.

PART 3 – EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

A. Compliance: Comply with manufacturer's product data, including product technical bulletins, product catalog installation instructions, and product carton instructions for installation.



3.2 EXAMINATION

- A. Site Verification of Conditions: Verify substrate conditions, which have been previously installed under other sections, are acceptable for product installation in accordance with manufacturer's instructions.

3.3 PREPARATION

- A. Surface Preparation: (Specify applicable product preparation requirements.)

3.4 ERECTION / INSTALLATION / APPLICATION / CONSTRUCTION

- A. Recycled Rubber Flooring Installation: Comply with Signature Sports Flooring Technical Manual for installation procedures and techniques for Signature Sports Flooring recycled rubber resilient flooring installation.
- B. Finish Color/Textures/Patterns: (Specify installation finishes coordinated with finishes specified in Part 2 Products.)
- C. Related Products Installation: Refer to other sections listed in Related Sections paragraph herein for related products installation.

3.5 FIELD QUALITY REQUIREMENTS

- A. Manufacturer's Field Services: Upon Owner's request, provide manufacturer's field service consisting of product use recommendations and periodic site visits for inspection of product installation in accordance with manufacturer's instructions.
 - 1. Site Visits: (Specify number and duration of periodic site visits.)

3.6 CLEANING

- A. Cleaning: Remove temporary coverings and protection of adjacent work areas. Repair or replace damaged installed products. Clean installed products in accordance with manufacturer's instructions prior to Owner's acceptance. Remove construction debris from project site and legally dispose of debris.

3.7 PROTECTION

- A. Protection: Protect installed product and finish surfaces from damage during construction.